

Great innovaphone IP6000 promotion!



While
stocks
last!

Save
almost
70 %

Previous price: EUR ~~4.800,00*~~

Current promotion price: EUR 1.500,00*

"IP6000 summer sale" at innovaphone

Summer brings a sensational special offer: The great innovaphone IP6000 promotion! Make the most of this offer and grab one of the last devices: the new IP6010's powerful predecessor now at an unbeatable price!

IP6000 promotion

You can buy the remaining IP6000 gateways for just EUR 1500.00* each while stocks last. Hurry and order the last devices now with a remarkable discount of almost 70 %.

Please note! PRI gateways now only with V8 upwards!

As the IP6000 will no longer be available, there will NO longer be an innovaphone PRI gateway which allows an installation under the innovaphone PBX Version 7 or older! The new gateway generation devices (IP6010, IP3010, IP0010) support installations from Version 8 upwards, enabling operation of a Linux Application Platform.

Interested?

Have we aroused your interest? Contact your innovaphone distributor, reseller or innovaphone contact person today to place your IP6000 order.

Comments

While stock last. Errors and omissions excepted.
All prices ex works subject to statutory VAT.
Hardware and Software purchases take place via the distributor.
* Prices and conditions are EUP recommendations to distributors.

Contact

innovaphone AG
Böblinger Straße 76 | 71065 Sindelfingen | Germany
Tel +49 7031 73009-0 | Fax +49 7031 73009-99
www.innovaphone.com | e-mail: info@innovaphone.com

Overview of the Features IP6000

- ✓ Suitable as hardware basis for innovaphone PBX
- ✓ Also for use by Provider and as Media Gateway
- ✓ 4 ISDN S_{2M} (PRI) interfaces, can be activated separately with licenses
- ✓ 2 x TE and 2 x NT Mode
- ✓ For loop through in 2 PRI lines with „power off loop“
- ✓ An additional ISDN S₀ (BRI) interface
- ✓ Two separate Ethernet interfaces, for IP routing, redundant networks
- ✓ With installation frame up to two devices in one 19 inch height unit
- ✓ Interconnection of several gateways possible with automatic load distribution
- ✓ Slot for compact flash as fileservers for announcements, voicemail and music on hold
- ✓ Encrypted configuration over web interface, update manager, diagnosis
- ✓ SIP and H.323 simultaneously, to provider and to the end devices
- ✓ Security: SRTP (voice), SIPS (signalling), HTTPS (admin)
- ✓ Low power consumption (12W)
- ✓ Integrated power supply 100-240V
- ✓ Power supply alternatively or redundantly with Power over Ethernet
- ✓ Extremely sturdy hardware, no rotating parts such as fans or hard disks

Order no.: 01-06000-024